


Hinged Door 472 Series







Designed with style and security in mind, the G.James 472 Series hinged door offers an attractive choice for main entry, balcony and exterior laundry room doors.

The 472 Series is the perfect low maintenance alternative to timber entry doors or, sliding doors where opening width is limited. Configurations include an expansive set of double doors or the economy of a single door - both can be combined with fixed side lights or overhead high lights to complete your entrance.

This door combines quality hardware with the uncompromising strength of heavy duty aluminium profiles to ensure you enjoy consistent long-term performance for years to come.

Left images: Cut-through of hinged door sills with optional barrier screen (guide only, subject to change without notice).



Hinged Door 472 Series

Features



Configurations







Hardware Options

Satin Chrome



Powder Coat White



Powder Coat Black



Screens


Flyscreens

G.James Flyscreens are an economical way to cover the open area of your windows and doors and help keep your home free from flies. Our flyscreens include an extruded aluminium frame with a standard fibreglass mesh.



Barrier Screens

All G.James Barrier Screens incorporate 7mm Armagrille (diamond-shaped, aluminium grille), standard flymesh and wider profile, aluminium frame. Black hardware and Armagrille are supplied as standard while keylock handles are fitted to all doors.



crimsate Crimsafe

Crimsafe screens allow you the freedom to leave your doors and windows open without compromising your security, disturbing your view or affecting airflow throughout your home. Black hardware and mesh supplied as standard.



Crimsafe is a registered trademark of Crimsafe Security Systems Pty Ltd.



Hinged Door 472 Series

Technical Data

Size Limitations¹

Max. Height: 3000mm

• Min. Width per Leaf: 700mm

Other Limitations

This product is not suitable for sheer wall or exposed positions

Max. Glass Thickness • 6.38mm Single Glaze / 20mm IGU

• 24mm (IGU)

Water

Performance

150 Pa without subsill, 450 Pa with subsill

Perimeter

Frame Width

100mm or 125mm

WERS Data²

U-Value range: 3.40 - 6.20 SHGC range: 0.26 - 0.63

Acoustics³

Up to Rw 31 (with 6.38mm laminated glass)

BAL

Tested and certified up to BAL-40

Compatible
Construction Types:

Brick Veneer, Clad Wall, Block Wall, Cavity Brick

and Modular/Transportable Home

IMPORTANT

Don't let the opportunity pass to consider your glass options.

G.James markets a wide selection of glass types to satisfy your individual needs for street appeal and address such issues as heat, noise, security and fading. For example, laminated glass is the perfect all-round 'performance' glass for reducing noise, eliminating UV rays (99%) and improving your security. All these benefits can be realised for less than you think - contact G.James on 132 877 for more information on choosing the right glass for you.



¹ The maximum size combination possible is dependent on the Window Rating or SLS/ULS requirement of the site. The above sizes are based on an N3 Window Rating Only. Consult your G.James Representative for further details

 $^{^2}$ Consult your G.James representative to determine the most suitable product configuration for your particular WERS / Section J requirements.

³ This is the maximum rating for this product and does not apply to all 132 Series Windows. Consult your G.James representative if a specific acoustic rating is required.