





Configurations

3 Leaf




4 Leaf



5 Leaf

5 Leaf Bi-fold Window
in one direction not available

6 Leaf



3L



3R



2L1R



1L2R




4L



4R



3L1R




1L3R



2L2R



4L1R



1L4R



3L2R




2L3R



6L



6R



4L2R



2L4R



3L3R



Product	Max. Height (mm)	Min. Width per Leaf (mm)	Max. Width per Leaf (mm)	Other
477-530 Series Bi-fold Window (Note: Structural beam (by builder) required for windows exceeding 2500mm in width or 20kg per leaf. See also first note below).	2100	450	1000	<ul style="list-style-type: none"> › Max. weight per leaf – 40 kg. › Standard Sill, Flush Sill (FS) & No Sill (NS) options available. › FS & NS windows are suitable for sheltered, non-exposed positions only. › NS windows have configuration restrictions.

Product Specific Notes:

- All beams are to be supplied by the builder and engineered with a maximum 3mm sag when subjected to live and dead loads.
- Bi-fold Door/Window combinations are also possible however these units are suitable for sheltered, non-exposed positions only.
- Consult your G.James representative regarding configurations greater than 5 leaves to determine the most suitable configuration for your situation.
- Internal screening is available upon request, limitations apply.