

G.James ColourLite range of painted glass allows a truly distinctive impression to be created with individual design concepts.

FEATURES

- Unlimited design options
- Complete creative control
- Expansive range of colours
- Excellent scratch resistance
- Tight registration of double images
- Durable finish
- Fade resistant

APPLICATIONS

- Building façades
- Interior fitout
- Overhead glazing
- Dot matrix borders (automotive/marine)
- Signage
- Artwork

HOW TO SPECIFY

Select
GJ ColourLite
Product name
Refer to size availability, file setup and application chart

G.James ColourLite range of glass provides options to meet any design requirements.



GJ COLOURLITE SCREEN

SIZES	STANDARD COLOURS	
Min 300mm x 200mm Max 4000mm x 2400mm	White Black Charcoal (PMS 7546) Cement Grey (PMS 427)	Basalt (PMS Cool Grey 10) Gannet (PMS Cool Grey 11) Pewter (PMS 422)
	Custom colour matching to standard PANTONE® or RAL colour range available on request	

GJ COLOURLITE GRAPHIC

SIZES	DIGITAL FILES (VECTOR FILES)
Min 300mm x 200mm Max 4000mm x 2400mm	Format: DWG, PDF, EPS or AI Colour space: RGB or CMYK Spot colours other than the standard range to be replaced with suitable RGB or CMYK colour values Convert text to outlines

GJ COLOURLITE IMAGE

SIZES	DIGITAL FILES (BITMAP & VECTOR FILES)
Min 300mm x 200mm Max 4000mm x 2400mm	Vector Format: DWG, PDF, EPS or AI Bitmap Format: PSD, JPG or TIFF Resolution: 720 DPI Colour space: RGB or CMYK Spot colours replaced with suitable RGB or CMYK colour values Convert text to outlines Image upscaling service available on request

GJ COLOURLITE DECO

SIZES	APPLICATION
Min 300mm x 200mm Max on request	Interior applications only Sizes, types, colours vary by application, contact your G.James representative

COLOUR MATCHING – GJ ColourLite inks have a unique colour gamut therefore we cannot guarantee the same accuracy in colour matching as traditional 4 colour process printing. GJ ColourLite Image and GJ ColourLite Graphic colour libraries should be referred to as a guide only.

GJ ColourLite Screen is not recommended for use in applications where back lighting may occur.

Contact G.James for applications where the painted surface is directly exposed to the elements or prolonged contact with moisture.

G.James does not recommend ceramic paint be applied to the surface of coated glass products.

Variation in perceived colour may occur with painted products. These variations will be more apparent with light colours viewed on site. The area behind the glass must be of a uniform colour to avoid shadowing or read through effects. To avoid potential issues, it is recommended that full size prototypes incorporating all specified spandrel materials are viewed on site.

Product warranty is subject to the relevant glazing application and should be discussed with G.James.

FREECALL 1800 452 637

Glass Products

ggames.com



Queensland

1007 Kingsford Smith Dr,
Eagle Farm QLD 4009

New South Wales

26 Long Street
Smithfield NSW 2164

Victoria

217 Rex Road,
Campbellfield VIC 3061

Other G.James Branches: (Qld) Eagle Farm, Logan City, Capalaba, Narangba, Ipswich, Gold Coast, Toowoomba, Sunshine Coast, Gympie, Hervey Bay, Bundaberg, Gladstone, Rockhampton, Mackay, Townsville & Cairns; (NSW) Sydney, Lismore, Newcastle, Taree & Queanbeyan; (SA) Adelaide; (NT) Darwin; (WA) Perth.

© 2017 G.James Glass & Aluminium. All rights reserved. The trademarks G.James, hexagon forming GJ and DEFINING SPACES are trademarks of G.James P/L ISO 9001:2008 Quality system in place at 1. Old Gympie Road, Narangba, QLD, 4504 2. Shed 23, Schneider Road, Eagle Farm, QLD, 4009 for G.James Safety Glass Pty Ltd (ABN 55010828065)