



The 076 Series is a high performance sliding window system suitable for residential, commercial and high rise applications.

Packaged within a standard frame width of 75mm (or optional 100mm frame – project specific), the 076 Series can achieve significantly higher water performance (when compared to the 132 Series) while also being the preferred sliding window system for accommodating IGU's.

This system combines clean architectural lines with integral strength to achieve a versatile, performance-orientated sliding window which promotes an aesthetically pleasing appearance while satisfying the desire for optimal visible light.

### Features

- Laboratory tested and NATA certified with 300, 450 & 800 Pa. water penetration options
- Glass thickness: Single glaze up to 13.52mm, IGU 20mm
- A range of interlocking mullions to satisfy nominated wind load
- Sash restrictors can be fitted where required to comply with the 'Protection of Openable Windows' act
- A standard jamb latch or upgrade to a flush-mounted, push button mortice lock (inside slide configurations only & not suitable for coastal environments). Keyed options available for both types
- Continuous jamb, window wall configurations possible.

### Product Matrix

- **Type - Inside Slide Standard Construction**
  - Water Penetration: Up to **300 Pa**.
  - Configurations: XO, OX, XOX, OXXO, XX & Window Walls
  - Screening: Fly & barrier screens positioned on outer track, interlock stiffeners to the outside. Security screens are face fixed to the exterior of the frame, interlock stiffeners to the inside. For XX configurations, all screening is face fixed to the frame exterior and cover the full area of the window.
- **Type - Inside Slide with Sub Sill**
  - Water Penetration: Up to **450 Pa**.
  - Configurations: XO, OX, XOX & OXXO
  - Screening: Fly & barrier screens positioned on outer track, interlock stiffeners to the outside. Security screens are face fixed to the exterior, interlock stiffeners to the inside. For XX configurations, all screening is face fixed to the frame exterior and covers the full window area.
- **Outside Slide Type**
  - Water Penetration: Up to **800 Pa**.
  - Configurations: XO, OX, XOX, OXXO & Window Walls
  - Screening: All screening is fixed to the frame exterior and cover the full area of the window, interlock stiffeners to the inside.

### Limitations

- **Window Size:**

Configuration	Max Height	Max Width	Max Area
OX, XO, XOX & XX	1870 mm	2640 mm	4.7 m <sup>2</sup>
OXXO	1870 mm	3300 mm	5.35 m <sup>2</sup>

Sizes are a guide ONLY and dependent on glass type and wind load requirements

- **Sash Weight:** up to 70 kg.



Inside Slide



Outside Slide